


014-0044**SGI 16s, Sight glass, Solder, ODF, 16 mm, Solder, ODF, 16.00 mm**

Inlet connection type: Solder, ODF, Inlet size [mm]: 16, Outlet connection type: Solder, ODF, Outlet size [mm]: 16.00

**PRODUCT DETAILS**

Gross weight	0.175 Kilogram
Net weight	0.149 Kilogram
Volume	0.277 Liter
EAN	5702422048534
Body material	Brass
China RoHS compliance	Yes exceed limitations
Connection material	Copper
Contain batteries	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Green: max moist con@25 °C	R22: 150 ppm
Green: max moist con@43 °C	R22: 250 ppm
Inlet connection type	Solder, ODF
Inlet size [in]	5/8 in
Inlet size [mm]	16 mm
Max. Working Pressure [bar]	35 bar
Max. Working Pressure [psig]	500 psig
Moisture indicator	I indicator
Other RoHS documentation	Saudi Arabia RoHS
Outlet connection type	Solder, ODF
Outlet size [in]	5/8 in
Outlet size [mm]	16 mm
Packing format	Multi pack
Product accessories	No
Product group	Sight glasses
Product Name Description	Sight glass
Quantity per packing format	28 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1) Cobalt dichloride (CAS no. 7646-79-9)
Refrigerants	R22
SCIP dossier no.	323c7b85-ff73-43cd-8fce-a44eabfb5297
Serviceable	No
Temperature range [°C] [max]	80 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	175 °F
Temperature range [°F] [min]	-58 °F
Type	SGI 16s

**PRODUCT DETAILS**

UK RoHS compliance	Out of scope
Yellow: min moist con@25 °C	R22: 300 ppm
Yellow: min moist con@43 °C	R22: 500 ppm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)